
ARES 8a Compact footprint. Huge performance.















nplete Rigging ution 0° to 10°

70Hz to 19kHz

ARES 8a is a compact, self-amplified 2-way touring system, renowned for its iconic sound signature in a wide range of sound reinforcement scenarios, from small concerts to theatre and stadium shows.

AUDIOFOCUS ARES 8a meets all WST criteria and offers the full benefits of a true line array. Dual 8" drivers handle low-mid frequencies, while a 1.4" exit compression driver coupled to a waveguide provides smooth high-end performance.

An advanced AUDIOFOCUS SCiO Class D amplifier module with integral DSP and 4 versatile presets allows ARES 8a to be quickly deployed in any configuration. The smart ARES rigging system lets a single operator set up an 8-element system in just 10 minutes, with angles ranging from 0° to 10° with a 0.5° step. ARES 8's lightweight construction and tough rubber handle make the system easy to carry, while magnetic pins cut out vibration.


ARES 8a is built with pride in Belgium and coated in tough, weather-resistant polyurea to safeguard your investment. The cabinet front is protected by a rigid metal grill, backed by acoustically transparent foam.


Technical specifications

Description	2-way self-powered full-range line array element	
Transducers	LF: 2 x 8" • HF: 1 × 3"	
Frequency range (-6dB)	70Hz-19kHz	
Nominal directivity (-6dB)	Horizontal 110° - Vertical: depends on the number of elements and array curvature.	
SPL max (1)	142 dB	
Processing	Dedicated AUDIOFOCUS presets	
Rigging	20 different inter-cabinet angle positions, from 0 to 10°	
Audio connectors	IN: 1×3-point XLR • LINK: 1×3-point XLR	
Network Connectors	1 x etherCON for control	
Power Connectors	IN: 1×3-point powerCON TRUE1TOP LINK: 1×3-point powerCON TRUE1TOP	
Dimensions (Including Rigging H x W x D)	244 x 643 x 396 mm • 9.61 x 25.3 x 15.60 inches	
Weight	30kg / 66.13lbs	
Finish	Highly resistant polyurea coating	
Cabinet	High grade birch plywood	

⁽¹⁾ Peak level measured at 1 m under free field conditions using pink noise with crest factor $5\,$


Dimensions






Rigging accessories


Bumper for ARES 8a and B 18a




Mini-bumper for ARES 8a




T-Yoke for ARES 8a



Overhat for ARES 8a



Protection cover for ARES 8



Subwoofers

S 18aTouring high performance self-powered 18" subwoofer.



Ref.: 48101 Ref.: 48

S 21aTouring high performance self-powered 21" subwoofer.



Ref.: 48103

B 18a Flyable, self-powered 18" touring Low-end extension. Fully compatible.




Ref.: 44323

Flight Cases

Flight-case for 2 ARES 8	Flight-case for 3 ARES 8	Flight-case for 3 ARES 8 with flying frame (not included)
Ref. : 45058	Ref. : 46479	Ref. : 41018
Flight-case for 4 ARES 8	Flight-case for 4 ARES 8 with	Flight-case for 2 flying frame

t-case for 4 ARES 8 flying frame (not included)



Flight-case for 2 mini flying frame ARES 8

Ref.: 46480



Software



SCiO Connect & Control your amplifiers

AUDIOFOCUS SCiO amplifiers can be securely monitored and controlled anytime, anywhere over the network.


Our intuitive Web UI network manager is web-based, eliminating the need for software downloads, and allows multiple amplifiers to be managed from your preferred device.

The network manager offers the comprehensive processing options you would expect from a high-end system controller.


For more detailed information **please visit the AUDIOFOCUS SCIO page.**

Beamwidth

ARES 8a Horizontal beamwidth



ARES 8a Vertical beamwidth



Contact & Links

Need more information about our products?

www.audiofocus.eu info@audiofocus.eu www.facebook.com/AudiofocusPage/ www.facebook.com/groups/AUDIOFOCUS/

Scan QR Code to view the ARES 8a product's web page.



Follow Us.





