







S 21i is a compact, high-performance passive subwoofer for fixed installations, designed to complement our FR-X, ARES 8 and ARES 12 series in theatres, houses of worship, live music venues, stadiums, and other sound reinforcement applications.

S 21i houses a long excursion 21" neodymium driver and combines front diffusion, bass reflex and transmission line design for maximum efficiency and outstanding SPL.

Deployed standalone, stacked, or flown, S 21i adapts to mirror the needs of the venue and offers huge space and weight savings compared to industrystandard 2×18" subs.

S 21i is built with pride in Belgium and coated in tough, weather-resistant polyurea to safeguard your investment. The cabinet front is protected by a rigid metal grill, backed by acoustically transparent foam.

S 21i can be quickly deployed in any configuration, including cardioid and end-fire, when used with AUDIOFOCUS A Series amplifiers. Armonia presets are also available for Powersoft amplifiers.

Technical specifications

Description	High-power Install 21" subwoofer
Transducers	LF: 1 x 21"
Frequency range (-6dB)	28Hz-100 Hz
SPL Peak (1)	139 dB
Processing	Dedicated AUDIOFOCUS and Armonia/Powersoft omni and cardioid presets
Rigging	M8 threated insert
Connectors	2 × 4-point speakON
Nominal Impedance	4ohm
Watt AES/peak	1700/7000W
Dimensions (H x W x D)	590 x 750 x 655 mm • 23.22 x 29.52 x 25.78 inches
Weight	58.8kg / 129.63lbs
Finish	Highly resistant polyurea coating
Cabinet	High grade birch plywood

(1) Peak level measured at 1 m under free field conditions using pink noise with crest factor 5

Accessories

S 21i side plate

Ref. : 48081

Related Speakers

ARES 8i Install 2-way line array loudspeaker



Ref. : 48113

FRX 15i Installation high performance 2-way bi-amp constant curvature



Ref. : 48117

Contact & Links

Need more information about our products?

www.audiofocus.eu

info@audiofocus.eu

www.facebook.com/AudiofocusPage/

www.facebook.com/groups/AUDIOFOCUS/

Scan QR Code to view the S 21i product's web page.



Follow Us.

