

118SG Ground stack 18" passive subwoofer



118SG is a compact, exceptionally powerful passive touring subwoofer, created as a core component of the AUDIOFOCUS ARRoCC 210 constant curvature and ELIZ 210 line array loudspeaker systems.

118SG is optimized for standalone and ground-stacked deployment, presenting a clean appearance and avoiding the weight and cost of integrated rigging hardware.

The subwoofer houses a next-generation 18" neodymium LF transducer. Tetracoil Double Voice Coil technology allows 118SG to achieve best-in-class SPL for its size while ensuring outstanding efficiency and clarity.

All AUDIOFOCUS loudspeakers are built in Belgium by skilled craftspeople and state-of-the-art machinery before being coated in tough, weather-resistant polyurea to safeguard your investment.



Complete solution



Omni and Cardioid



30Hz to 80Hz

Technical specifications

Description	High-power compact passive 18" subwoofer
Transducers	LF: 1 x 18" with Tetracoil Double Voice Coils
Frequency range (-6dB)	30Hz-80Hz
SPL peak (1)	135 dB
Processing	Dedicated AUDIOFOCUS and Armonia/Powersoft omni and cardioid presets
Rigging	Ground stack. Pole socket.
Connectors	2 x 4-point speakON (front) 2 x 4-point speakOK (rear)
Nominal impedance	8ohm
Watt AES/peak	1800/7200W
Dimensions (H x W x D)	580 x 700 x 700mm • 22.8 x 27.6 x 27.6 inches
Weight	70kg • 154.3lbs
Finish	Highly resistant polyurea coating
Cabinet	High grade birch plywood

(1) Sound pressure referenced to 1m in half space (2 pi)

Related Speakers

ARRoCC CC210Wx

2x10" passive constant curvature loudspeaker 90° x 25°



Ref. : 48434

ARRoCC CC210Nx

2x10" passive constant curvature loudspeaker 90° x 12.5°



Ref. : 48438

ELIZ 210

Touring 2x10" passive line array loudspeaker



Ref. : 48594

Contact & Links

Need more information about our products ?

www.audiofocus.eu

info@audiofocus.eu

www.facebook.com/AudiofocusPage/