

# 118SGa

High-power active ground stack 18" subwoofer

## Power and thermal specifications

| Power and Thermal 115 V        |            |
|--------------------------------|------------|
| Idle Power                     | 60W        |
| Idle Current Draw              | 0.6A       |
| Idle Thermal loss              | 204 BTU/h  |
| 1/8 Power @ 4 Ohm Power        | 1400W      |
| 1/8 Power @ 4 Ohm Current Draw | 7A         |
| 1/8 Power @ 4 Ohm Thermal loss | 1364 BTU/h |
| Power and Thermal 230V         |            |
| Idle Power                     | 60W        |
| Idle Current Draw              | 0.3A       |
| Idle Thermal loss              | 204 BTU/h  |
| 1/8 Power @ 4 Ohm Power        | 800W       |
| 1/8 Power @ 4 Ohm Current Draw | 3.5A       |

| Amplification and power supply |                                                    |
|--------------------------------|----------------------------------------------------|
| Amplification class            | Class D                                            |
| Power supply model             | Universal switch mode power supply with active PFC |
| Power Factor                   | > 0,9 above 1/2 P                                  |
| Mains Rating                   | 100-240V @ 50-60 Hz                                |
| Operating Voltage              | 90-260V                                            |
| AC Mains connector             | powerCON TRUE1TOP (16A)                            |