

115SG

Ground stack 15" passive subwoofer



115SG is a compact, powerful passive touring subwoofer, created to complement multiple short-medium throw AUDIOFOCUS ranges, including the Cyris CX8 and Isolde AP108 point source loudspeakers.

115SG is designed for standalone and ground-stacked deployment, with a pole-mount socket allowing easy mounting of top cabinets.

The subwoofer houses a next-generation 15" neodymium LF transducer. Tetracoil Double Voice Coil technology allows 115SG to achieve best-in-class SPL for its size while ensuring outstanding efficiency and clarity.

All AUDIOFOCUS loudspeakers are built in Belgium by skilled craftspeople and state-of-the-art machinery before being coated in tough, weather-resistant polyurea to safeguard your investment.



Complete solution



Omni and Cardioid



35Hz to 100Hz

Technical specifications


| | |
|------------------------|--|
| Description | High-power passive ground stack 15" subwoofer |
| Transducers | LF: 1 x 15" with Tetracoil Double Voice Coils |
| Frequency range (-6dB) | 35Hz-100Hz |
| SPL peak (1) | 131 dB |
| Processing | Dedicated AUDIOFOCUS and Armonia/Powersoft omni and cardioid presets |
| Rigging | Ground stack. Pole mount socket. |
| Connectors | 2 x 4-point speakON (front) 2 x 4-point speakON (rear) |
| Nominal impedance | 8ohm |
| Watt AES/peak | 900W / 3600W |
| Dimensions (H x W x D) | 500 x 595 x 600mm • 19.7 x 23.4 x 23.6 inches |
| Weight | 38.5kg / 84.9lbs |
| Finish | Highly resistant polyurea coating |
| Cabinet | High grade birch plywood |

(1) Tone Burst CEA2010B-Standard

Related Speakers

ISOLDE AP108x

Touring 2-way 8" passive point source loudspeaker



Ref.: 48449

ISOLDE AP108ix

Installation 2-way 8" passive point source loudspeaker



Ref.: 48451

CYRIS CX8

Compact 8" coaxial passive point source loudspeaker



Ref.: 48690

Contact & Links

Need more information about our products ?

www.audiofocus.eu

info@audiofocus.eu

www.facebook.com/AudiofocusPage/